

Material Safety Data Sheet

Kodak Polychrome
GRAPHICS

229 Image Remover

1. Chemical Product and Company Identification

Common Name : 229 Image Remover

Synonym : Not available.

Catalog number : 1076702

Area of Application : Industrial applications. Graphic Arts Imaging.

Supplier : Kodak Polychrome Graphics
401 Merrit 7
Norwalk, CT 06851
USA
Tel. (203) 845-7000

Emergency telephone number : **In Case of Emergency (medical/roadside) (24hrs)**

For other EHS Information : Kodak Polychrome Graphics, Environmental Solutions Department;
11465 Johns Creek Parkway, #260, Duluth, GA 30097; USA
Phone: 1-877-574-7274 ext. 511, Additional phone: (770) 232-2133
E-mail: PEP@kgraphics.com, Fax: (770) 232-2150;

MSDS#	511
Version	2.61
Validation Date	2003-02-03
Responsible Name	Kodak Polychrome Graphics

KPG# **70021**

CALL 1-800-451-8346

2. Composition, Information on Ingredients

Name	CAS #	% by Weight	Exposure Limits
1) Cyclohexanone	108-94-1	45-50	NOM-010-STPS (Mexico, 1999). STEL: 400 mg/m ³ 15 minute(s). TWA: 200 mg/m ³ 8 hour(s). ACGIH (United States, 2002). Skin TWA: 100 mg/m ³ 8 hour(s). NIOSH REL (United States, 1994). Skin TWA: 100 mg/m ³ 10 hour(s). OSHA (United States, 2001). TWA: 200 mg/m ³ 8 hour(s). Not available.
2) Water	7732-18-5	40-45	Not available.
3) Methyloxirane-oxirane copolymer	9003-11-6	1-5	Not available.
4) Ammonium hydrogen bifluoride	1341-49-7	4	ACGIH (United States, 2002). TWA: 2.5 mg/m ³ 8 hour(s). Form: As F NIOSH REL (United States, 1994). TWA: 2.5 mg/m ³ 10 hour(s). Form: As F OSHA (United States, 2001). TWA: 2.5 mg/m ³ 8 hour(s). Form: As F

3. Hazards Identification

Physical State and Appearance : Liquid.

Emergency Overview : CAUTION!
COMBUSTIBLE LIQUID AND VAPOR.
HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS AND IRRITATION OF THE EYES OR RESPIRATORY TRACT.
HARMFUL IF SWALLOWED.
MAY CAUSE EYE IRRITATION.
CAN CAUSE CARDIAC EFFECTS
THE TOXICOLOGICAL PROPERTIES OF THIS MATERIAL HAVE NOT BEEN FULLY INVESTIGATED.
Avoid breathing vapors or spray mists. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash thoroughly after handling.

Routes of Entry : Absorbed through skin. Dermal contact. Eye contact. Inhalation.

Potential Acute Health Effects

Eyes : Slightly hazardous in case of eye contact (irritant).

Continued on Next Page

<i>Skin</i>	: Low hazard for recommended handling
<i>Inhalation</i>	: Hazardous in case of inhalation.
<i>Ingestion</i>	: Harmful if swallowed.
Potential Chronic Health Effects	: CARCINOGENIC EFFECTS: Classified None. by OSHA, None. [Cyclohexanone]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Cyclohexanone]. Classified None. by OSHA, None. [Ammonium hydrogen bifluoride]. Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Ammonium hydrogen bifluoride]. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.
Medical Conditions Aggravated by Overexposure:	: Repeated or prolonged exposure is not known to aggravate medical condition.
See Toxicological Information (section 11)	

4. First Aid Measures

Eye Contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Seek medical attention.
Skin Contact	: After contact with skin, wash immediately with plenty of water. Get medical attention if symptoms occur.
Inhalation	: Allow the victim to rest in a well-ventilated area. If irritation persists, seek medical attention.
Ingestion	: Do not induce vomiting. Have conscious person drink several glasses of water or milk. Seek immediate medical attention.

5. Fire Fighting Measures

Flammability of the Product	: COMBUSTIBLE.
Auto-Ignition Temperature	: The lowest known value is 420°C (788°F) (Cyclohexanone).
Flash Points	: CLOSED CUP: 53°C (127.4°F).
Flammable Limits	: The greatest known range is LOWER: 1.3% UPPER: 9.4% (Cyclohexanone)
Hazardous thermal (de)composition products	: These products are carbon oxides (CO, CO ₂). Ammonia. halogenated compounds
Fire Hazards in Presence of Various Substances	: Slightly flammable to flammable in presence of open flames, sparks and static discharge, of heat.
Explosion Hazards in Presence of Various Substances	: Risks of explosion of the product in presence of mechanical impact: Not available. Slightly explosive in presence of open flames, sparks and static discharge.
Fire Fighting Media and Instructions	: Use DRY chemicals, CO ₂ , water spray or foam.
Protective Clothing (Fire)	: Be sure to use an approved/certified respirator or equivalent.
Special Remarks on Fire Hazards	: May emit toxic fumes under fire conditions.

6. Accidental Release Measures

Small Spill and Leak	: Absorb with an inert material and place in an appropriate waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.
Large Spill and Leak	: Absorb with an inert material and place in an appropriate waste disposal container. Neutralize with a dilute sodium carbonate solution. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

7. Handling and Storage

- Handling** : Do not ingest. Avoid breathing vapors or spray mists. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash thoroughly after handling.
- Storage** : Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Keep container tightly closed.

8. Exposure Controls, Personal Protection

- Engineering Controls** : Use good general ventilation (>10 air changes/hour) and engineering controls (local exhaust, filter's, process enclosures if necessary) to maintain airborne levels below ACGIH Threshold Limit Values (TLV) and OSHA Permissible Exposure Limits (PEL). Ensure that eyewash station and safety shower is proximal to the work-station location.

Personal Protection

- Eyes** : Safety glasses.
- Body** : Not applicable.
- Respiratory** : Vapor respirator.
- Hands** : Gloves (impervious).
- Feet** : Not applicable.

Protective Clothing (Pictograms)



- Personal Protection in Case of a Large Spill** : Splash goggles. Lab coat. Gloves (impervious). Vapor respirator.

Product Name

1) Cyclohexanone

Exposure Limits

NOM-010-STPS (Mexico, 1999).

STEL: 400 mg/m³ 15 minute(s).

TWA: 200 mg/m³ 8 hour(s).

ACGIH (United States, 2002). Skin

TWA: 100 mg/m³ 8 hour(s).

NIOSH REL (United States, 1994). Skin

TWA: 100 mg/m³ 10 hour(s).

OSHA (United States, 2001).

TWA: 200 mg/m³ 8 hour(s).

Not available.

Not available.

ACGIH (United States, 2002).

TWA: 2.5 mg/m³ 8 hour(s). Form: As F

NIOSH REL (United States, 1994).

TWA: 2.5 mg/m³ 10 hour(s). Form: As F

OSHA (United States, 2001).

TWA: 2.5 mg/m³ 8 hour(s). Form: As F

2) Water

3) Methyloxirane-oxirane copolymer

4) Ammonium hydrogen bifluoride

Consult local authorities for acceptable exposure limits.

9. Physical and Chemical Properties

Physical State and Appearance : Liquid. **Odor** : Sweet.

Color : White.

pH : 5.2 [Acidic.]

Boiling/Condensation Point : >100°C (212°F)

Melting/Freezing Point : <0°C (32°F)

Specific Gravity : 0.994 (Water = 1)

Vapor Pressure : The highest known value is 0.3 kPa (2 mmHg) (at 20°C) (Cyclohexanone).

Vapor Density : The highest known value is 3.4 (Air = 1) (Cyclohexanone).

VOC Calculated : 479.37 g/l (4 lbs/Gal.).

- Dispersion Properties** : See solubility in water.
- Solubility** : Easily soluble in cold water.

10. Stability and Reactivity

- Stability and Reactivity** : The product is stable.
- Conditions of Instability** : Not available.
- Incompatibility with Various Substances** : Incompatible with some alkalis. Incompatible with some strong acids. Incompatible with strong oxidizing agents.
- Hazardous Decomposition Products** : These products are carbon oxides (CO, CO₂). Ammonia. halogenated compounds
- Hazardous Polymerization** : Will not occur.

11. Toxicological Information

- Toxicity to Animals** : **Cyclohexanone:**
 ORAL (LD50): Acute: 1535 mg/kg [Rat].
 DERMAL (LD50): Acute: 948 mg/kg [Rabbit].
 VAPOR (LC50): Acute: 8000 mg/l 4 hour(s) [Rabbit].
Water:
 ORAL (LD50): Acute: >90000 mg/kg [Rat].
Methyloxirane-oxirane copolymer:
 ORAL (LD50): Acute: >5000 mg/kg [Rat].
Ammonium hydrogen difluoride
 LD50: Not available.
 LC50: Not available.
- Chronic Effects on Humans** : Not available.
- Other Toxic Effects on Humans** : Slightly hazardous in case of eye contact, of inhalation (irritant).
 Hazardous in case of ingestion.

12. Ecological Information

- Organics Readily Degradable (70%)** : Not available.
- Ecotoxicity** : Ecotoxicity in water (LC50): 536 mg/l, 96 hours [Fish]. (Cyclohexanone). 820 mg/l, 48 hours [Daphnia]. (Cyclohexanone). 203 mg/l, 96 hours [Fish (Trout)]. (Methyloxirane-oxirane copolymer). >100 mg/l, 96 hours [Fish]. (Ammonium hydrogen difluoride).
- Toxicity of the Products of Biodegradation** : The products of degradation are less toxic than the product itself.

13. Disposal Considerations

- Waste Information** : Waste must be disposed of in accordance with federal, state and local environmental control regulations.
 Consult your local or regional authorities.

14. Transport Information

- DOT Classification** : Exempt as a combustible liquid.



- TDG Classification** : CLASS 3: Flammable liquid.

- ADR/RID Classification** : ADR Class: Flammable liquid with a flash point between 21°C (70°F) and 100°C (212°F).

IMO/IMDG Classification : IMDG Class 3: Flammable liquid.
Proper shipping name : FLAMMABLE LIQUID, N.O.S. (Cyclohexanone)
UN number : UN1993
Packing Group : III
ICAO/IATA Classification : IATA Class 3: Flammable liquid.
Proper shipping name : FLAMMABLE LIQUID, N.O.S. (Cyclohexanone)
UN number : UN1993
Packing Group : III

15. Regulatory Information

HCS Classification : Class: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).

U.S. Federal Regulations : TSCA 8(b) inventory: All the ingredients are on the TSCA list.
 SARA 302/304/311/312 extremely hazardous substances: No products were found.
 SARA 302/304 emergency planning and notification: No products were found.
 SARA 302/304/311/312 hazardous chemicals: No products were found.
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Cyclohexanone: Fire Hazard, Immediate (Acute) Health Hazard; Ammonium hydrogen bifluoride: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard
 SARA 313 toxic chemical notification and release reporting: No products were found.
 Clean Water Act (CWA) 307: No products were found.
 Clean Water Act (CWA) 311: No products were found.
 Clean air act (CAA) 112 accidental release prevention: No products were found.
 Clean air act (CAA) 112 regulated flammable substances: No products were found.
 Clean air act (CAA) 112 regulated toxic substances: No products were found.

International Regulations

WHMIS (Canada) : CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
 CLASS D-2B: Material causing other toxic effects (TOXIC).

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

CEPA DSL: All the ingredients are on the DSL list.

DSCL (EEC) : R10- Flammable.
 R20/22- Harmful by inhalation and if swallowed.
 R34- Causes burns.

International Lists : Not available.

State Regulations : Pennsylvania RTK: Cyclohexanone; Ammonium hydrogen bifluoride
 Florida: Cyclohexanone
 Massachusetts RTK: Cyclohexanone; Ammonium hydrogen bifluoride
 New Jersey: Cyclohexanone; Ammonium hydrogen bifluoride
 California prop. 65: No products were found.

16. Other Information

Label Requirements : COMBUSTIBLE LIQUID AND VAPOR.
 HIGH VAPOR CONCENTRATIONS MAY CAUSE DROWSINESS AND IRRITATION OF THE EYES OR RESPIRATORY TRACT.
 HARMFUL IF SWALLOWED.
 MAY CAUSE EYE IRRITATION.
 CAN CAUSE CARDIAC EFFECTS
 THE TOXICOLOGICAL PROPERTIES OF THIS MATERIAL HAVE NOT BEEN FULLY INVESTIGATED.

Hazardous Material Information System (U.S.A.)	Health	2
	Fire Hazard	2
	Reactivity	0
	Personal Protection	G

National Fire Protection Association (U.S.A.)



References : Not available.

Other Special Considerations : Not available.

Validated by Kodak Polychrome Graphics on 2003-02-03.

Verified by Kodak Polychrome Graphics.

Printed 2003-02-03.

In Case of Emergency CALL 1-800-451-8346

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

FOR INDUSTRIAL USE ONLY